



## CLB160/CLB180

### Chain Series



### Specifications

| Model              | CLB160                         |             | CLB180               |             |             |
|--------------------|--------------------------------|-------------|----------------------|-------------|-------------|
| Wattage            | 60W                            |             | 80W                  |             |             |
| Input Voltage      | AC 100~277V, 50/60Hz           |             | AC 100~277V, 50/60Hz |             |             |
| CCT                | 5700K                          | 3000K       | 5700K                | 3000K       |             |
| Field Angle        | 120°                           |             | 120°                 |             |             |
| Flux               | 4600 lm                        | 3800 lm     | 6200 lm              | 5200 lm     |             |
| Luminous Intensity | Lux@1M                         | 1350 Lux@1M | 1000 Lux@1M          | 1900 Lux@1M | 1520 Lux@1M |
|                    | Lux@2M                         | 330 Lux@2M  | 250 Lux@2M           | 475 Lux@2M  | 380 Lux@2M  |
|                    | Lux@3M                         | 140 Lux@3M  | 110 Lux@3M           | 200 Lux@3M  | 168 Lux@3M  |
|                    | Lux@4M                         | --          | --                   | --          | --          |
| CRI                | 70                             | 80          | 70                   | 80          |             |
| Dimension          | <p>D: 315 mm<br/>H: 185 mm</p> |             |                      |             |             |
| Weight             | 1440 g ± 10%                   |             |                      |             |             |
| Lifetime           | 30,000 hours                   |             |                      |             |             |
| Warranty           | 1-Year                         |             |                      |             |             |